## Limit Breakers


#### Smart Robotics, Boundless Possibilities

## Technical Overview


- Chasis Dimensions: 25 \* 25\* 26 cm
- Motor Control: Arduino Mega PID
- RPLidar A1 2D scanner
- Li-lon (4\*3.7v) 14.8 v Power Supply
- > Processor: Raspberry Pi 4
- Communication: UART

### Raspberry Pi

Mini computer for robot control and navigation.



Drives the robot's wheels.



**Motor Drivers** 

Rpidar A1

2D laser scanner for mapping

and object detection.

Hardware for motor control [speeds & direction].

## Achievements

#### Stable and Efficient Design

A narrow track width for improved stability

Three layer chassis with large area for packaging electronic components [heavy ones at the bottom and Middle layers].

control.

#### **Optimized Traction**

Thick wheels closely -arranged together with large treads improve traction and maneuverability on various terrains.

Arduino Mega

Microcontroller for

hardware and motor

Two caster wheels close to the main wheels to achieve stability.

#### **Streamlined Build**

A Slim design with three layer chassis for achieving high maneuverability in tight spaces.

#### **Automated Mapping**

Our robot autonomously maps its environment using advanced SLAM technology, with integrated path planning and real-time sensor data for precise navigation and efficient exploration.




#### Robot Creation from design to implementation

# 25 cm 25 cm Thick wheels with large treads 65cm \*26cm


## Visualization

#### Gazebo [virtual]



A visualization of the robot in a virtual environment

## **RViz** [Real time]



This is a representation of the map according to the Rpidar scanner

