# Team Syzygy Autonomous Mapping & Navigation Robot

Brian Macharia, Kennedy Wahome, and Lenny Ng'ang'a Mechatronics Engineering | Electrical & Electronics Engineering | Control & Instrumentation

### **Abstract**

This paper introduces our custom-designed mapping and navigation robot, developed specifically for SLAM (Simultaneous Localization and Mapping) applications within a provided maze gamefield


By integrating advanced sensors and autonomous navigation capabilities, our robot enhances situational awareness and operational efficiency in challenging environments, crucial for search and rescue operations.

### Introduction

**Objective:** Our robot aims to provide efficient, reliable, and autonomous tools that improve operational outcomes through effective SLAM techniques.

**Rising Demand:** The need for advanced mapping and navigation solutions has surged, especially in search and rescue operations due to increasing natural disasters.

### Methodology - II






Fig. 3: Wheel-Encoder attachment

# SLAM Implementation PROS Fig. 5: Robot Operating System (ROS) TOPIC Node 1






Fig. 7: Navigation Stack 2 (Nav2)

### Challenges

- Steep learning curve for ROS2 adoption (Robotics Dojo Community)
  - Providing training and guidance
  - Providing open-source resources e.g. code, simulation tooling, and docker image

### Acknowledgements

- Special thanks to the Japan International Cooperation Agency (JICA) for resource support.
- Acknowledgment to Dr. Shohei Aoki, Ph.D., for guidance during research and development.

### **Future Work**

- SLAM + Object Detection
- Visual Simultaneous Localization & Mapping (VSLAM)





Fig. 8: Intel Realsense D435i

Fig. 9: Object Detection (cats and dogs)

### Methodology - I

### **Agile Methodology**




Fig. 1: Agile Methodology Chart

### **Vehicle Design**

- Design Requirements:
  - Short fabrication time Laser Cutting vs 3D Printing
  - Simple physical model Circular Chassis
  - Competition Guidelines

### **SLAM Implementation**

- Key Components:
  - RPLiDAR A1 (LiDAR sensor) for accurate mapping.
  - Wheel encoders for precise localization.L298N motor driver.
  - Raspberry Pi 4 and Arduino Mega 2560 for processing.
- Fig. 4: Gazebo Simulation Environment


## Experimental Results

- Modular Development Approach:
  - o Individual units developed first e.g. individual motors programmed
  - Individual functional units next e.g. motor control in all 4 directions
  - Individual subsystems e.g. driving motors via tele-operation nodes
- Testing Approach:
  - Unit testing of individual nodes (e.g., LiDAR data visualization).
  - Integration testing of the entire robot (e.g., teleoperation within the maze).
- Mapping Integration: Final integration of SLAM functionality tested on the maze gamefield to ensure effective navigation and mapping.
- A custom simulation environment was built on Gazebo and RViz and this enabled the rapid testing of ROS2 mapping and navigation packages.

### **Contact Information**

For further inquiries or collaboration opportunities, please reach out to our team via the details below (or scan the QR code to get all contact details)

- Brian Macharia (Team Leader)
- o brian.macharia.wambui@gmail.com
- Kennedy Wahome
- kennedywahome.24@gmail.comLenny Ng'ang'a



o codewithlennylen254@gmail.com




Fig. 10: Team Syzygy Contact Information